

new eagle



RAPTOR®  
INNOVATION  
SUMMIT 2025


# Raptor Universe 2025

Presented by:  
Parker Mosman, Chief Product Officer, New Eagle



# Where We're Going

- 01** A Year In Review (Hardware)
- 02** A Year In Review (Software)
- 03** Expanding Software Development Environments
- 04** Future Hardware Launches
- 05** What's Next



# A Year In Review (Hardware)



# 2025 ECU Launches



Already Available As Of Raptor 2024b v2.0

To Be Released In Raptor 2025b

## GCM108 (M2-501)



High channel count hydraulic controller with powerful compute

- 16x independent hydraulic control channels
- Powerful 3 core TC277 MCU
- 20x high side channels
- Automotive ethernet & 3x CAN-FD



## GCM44 (M2-031)



Cost optimized hydraulic controller ideal for distributed systems

- 2 independent hydraulic control channels (potential for 4)
- Single core TC234 MCU
- 3x high side channels
- 2x CAN-FD



## GCM112 (M2-411)



High-performance general-purpose ECU

- Powerful 3 core TC377 MCU with 300MHz cores
- Integrated accelerometer
- Balanced mix of inputs and outputs
- 2x CAN-FD



## CCM112



High-performance fail operational gateway controller

- Dual TC397 and TC377 MCUs linked via SPI/HSSL
- 8x shared CAN-FD & 2x independent automotive ethernet
- 24x high side channels
- Advanced security functions powered by ETAS CycurHSM



# Active ECU Portfolio

## Our ECU portfolio scales to meet your performance, I/O, and cost requirements

- MCUs ranging from single core Z0 PowerPC through six core with four lockstep TriCore
- Covers a wide range of application domains with a single toolchain, including:
  - Power distribution
  - Rugged hydraulic control
  - Supervisory & vehicle control
  - Basic & advanced gateway applications
  - Fuel cell control
- Options for functional safety and cybersecurity span the portfolio
- All newly added ECUs supported by a single compiler license (HighTec TriCore Platform Compiler) and a common OS (ETAS RTA-OS)



GCM48



RCM80



RCM112



CCM112



GCM44



GCM56



GCM111



GCM112



GCM106

*Support for all highlighted ECUs added since Raptor 2023a!*



GCM108



# A Complete E/E Architecture With A Single Toolchain


## Raptor can now solve (almost) all of your problems

Dramatically streamline development time and reduce program risk by commonizing on a single toolchain

- Move IP freely between ECUs in minutes
- Leverage common communication functions to establish safe and secure communication in minutes
- Drive out the inefficiencies of managing multiple application development environments within a single vehicle development team

Recoup toolchain investment time and time again

- Raptor and relevant add-on products support all ECUs in the portfolio through a single license
- Includes Raptor-Safe tooling



# A Year In Review (Software)





# 2025 Raptor Enhancements

Substantial enhancements available in Raptor 2025b

## J1939-21 <-> J1939-22 Gateway

Seamlessly translates data between legacy high-speed CAN and CAN-FD networks

- Raptor handles message format translation between -21 and -22 networks
- Configurable via Vector DBC file or graphical interface
- Supports functional safety and cybersecurity payload fields
- Presently supported on RCM112 and CCM112. Support coming to additional targets.

## J1939-91C Support

Raptor supports next generation J1939 cybersecurity features today

- Raptor supports the network leader persona with network follower support coming later
- Supported on RCM112 based on software cryptography
- Support for CCM112 based on hardware security module (HSM) implementation leveraging ETAS CycurHSM available in Raptor 2025b

## DoIP Gateway

Dramatically reduces OTA update and remote diagnostic complexity

- New Eagle ECU serves as interface between telematics unit and rest of the vehicle
- Raptor translates DoIP frames on Ethernet to UDS frames on CAN
- “Near zero” programming required at Raptor level
- Presently supported on RCM112. Support coming to CCM112, GCM106, & GCM108

Supported in Raptor 2025a

## Raptor Astrée

Ensures generated code is free from run-time defects

- Able to detect divide by zero, index out of bounds, dereference of uninitialized pointer, and many others
- Configurable to check MISRA, CERT-C, and other common rulesets as part of analysis
- Configurable to compute software metrics such as cyclomatic complexity, number of returns, and comment density

# DoIP Gateway Architecture


## Raptor powered ECUs drastically reduce complexity of OTA updates

New Eagle ECU serves as gateway between the vehicle telematics unit and downstream ECUs

- DoIP protocol allows for high-speed communication on two wires between TCU and New Eagle gateway
- New Eagle ECU routes traffic to appropriate CAN bus containing the target ECU
- Process can play out while the same New Eagle ECU performs other advanced control functions

Supports both OTA reprogramming and remote diagnostic functions

- Also supports 3<sup>rd</sup> party ECUs
- Future Raptor updates will add support for gateway function to additional New Eagle ECUs



# Advanced J1939 Support


## Raptor seamlessly handles protocol translation while your App keeps working

Legacy J1939-21 networks incompatible with J1939-22

- The -22 standard forbids -21 messages on a -22 network
- The -22 standard uses a newly imagined frame format to maximize CAN-FD network utilization
- One -22 frame can contain many -21 payloads

Raptor eliminates the need for user code to manage this translation process

- Includes the ability to attach E2E and SecOc to data payloads
- Optimized for multicore processing to keep application cores available for complex control functions
- Translation works in both directions, not just -21 -> -22






# Raptor Safe Recap

All referenced ECUs supported in Raptor Safe as of Raptor 2025a

## Raptor Stack Check: Uses the executable produced by Raptor to compute worst case stack consumption for each task and ISR

- Enabled by the addition of a single Raptor block to your model
- Output available in plain text in Simulink, as well as highly configurable reports with navigable call graphs
- Handles dual stack on TriCore targets
- A single license today supports RCM112, CCM112, RCM80, GCM48, GCM111, GCM106, and GCM56, with more targets added constantly




### Worst-case 'System' stack history : stack\_check\_Os\_Entry\_task\_asw0\_20ms

```

-> 0 < 8> 'Os_Entry_task_asw0_20ms'
-> 8 < 8> 'App_Rtos_McOTask20ms@raptor_gen.c'
-> 16 < 0> 'Timer_Task_20ms'
-> 16 < 4280> 'RaptorSafeLunchNLearn_Task_20ms'
-> 4296 < 0> 'powf'
-> 4296 < 152> '_FPow'
-> 4448 < 80> '_FXp_mulh'
-> 4528 < 72> '_FXp_addh'
-> 4600 < 24> '_FDunscale'
-> 4624 < 0> '_FDnorm'
=> 4624 bytes of stack
    
```

## Raptor Time Check: Uses the executable produced by Raptor to estimate worst case execution time for each task and ISR

- Enabled by the addition of a single Raptor block to your model
- Output available in plain text in Simulink, as well as highly configurable reports with navigable call graphs
- Key assumptions impacting performance configurable at Raptor level, such as cache hit model
- A single license today supports CCM112, GCM48, RCM80, and RCM112, with more targets added constantly



```

### Building source files...
### Generating Raptor Check annotation file(s) for analysis type time_check.
### Generating Raptor Check project file for analysis type time_check.
RPG NOT CREATED : The Generate Code Only model setting is enabled. Click here to disable this option.

Build Number: 45
Build Time: 22.8 seconds.

##### Successful Raptor Build #####

### Starting Raptor Time Check
Elapsed time is 0.039366 seconds.
### Finished Raptor Time Check

##### Error During Raptor Build #####
Jul 12, 2024 08:24:34
    
```



# Introducing Raptor Astrée

Raptor Astrée Already Supported on RCM112 and CCM112 in Raptor 2025a

## Validate Your Code



Formally prove the absence of:

- Divide by zero, index out of bounds, arithmetic overflow/underflow, and other common defects
- Data races in both single core and multi core contexts
- Use of uninitialized memory (e.g. pointers)

Saves thousands of manhours lost to iterative development when bugs are discovered later in the process

Qualification kit for ISO 26262 available

## Standardize Your Code



Ensure your code complies with numerous standards through automation

- MISRA-C, CERT-C, CWE, etc.
- Adaptable to support checking your own internal coding standards
- Highly configurable report generation with ability to document justifications for each finding

Streamlines internal code review process by removing debate on naming and syntactic decisions

## Measure Your Code



Automate software quality processes through automatic metric calculations, including:

- Cyclomatic complexity
- Comment Density
- Number of return statements
- And many more

Add user defined alarm thresholds for key metrics to further streamline code review process

# Expanding Software Development Environments





# One Toolchain, Many Targets

Toolchain			
Compiler	 For TriCore	 For Power Architecture 	
OS			
Targets	 <p>CCM112</p>	 <p>RCM112</p>	



# But, Why Only One Toolchain

<p>Toolchain</p>	 <div style="border: 2px solid red; padding: 5px; display: inline-block;">    </div>  <p>Expanding the ways in which customers can interact with New Eagle hardware</p>		
<p>Compiler</p>		 	
<p>OS</p>			
<p>Targets</p>	 <p>CCM112</p>	 <p>RCM112</p>	


# Announcing CODESYS v3 Support On New Eagle ECUs

## CODESYS will be progressively supported on all ECUs based on Infineon TriCore

Ideal for companies developing in IEC programming languages or with relatively basic control problems to solve

- Supports ladder logic, structured text, and other IEC 61131-3 formats
- Eliminates need for commercial compiler licenses (i.e. \$0 compiler cost)
- CODESYS IDE fully integrates the ability to develop, build, and download code, as well as acquire data and calibrate parameters at run-time
- Download and debug via ethernet available on supported targets
- CODESYS license included in the purchase price of the ECU (i.e. \$0 incremental toolchain cost)

New Eagle's implementation supports CANopen master & slave protocols, as well as J1939.



*CODESYS Support Coming To All Of These Great ECU Platforms In the Coming Months*



GCM44



GCM56



GCM111




GCM112




GCM106

*Already Available As A CODESYS ECU Today!*



CCM112



GCM108

# Pictorus Support Is Coming to Select New Eagle ECUs

## Pictorus is a model-based design tool that generates Rust code instead of C

Support for Rust code generation has potential to accelerate the development of safety critical systems


- Rust compiler includes a static analyzer to detect runtime defects
- Rust offers streamlined memory safety
- Rust offers built-in support for concurrency management

The Pictorus environment offers intuitive model-based development accessible directly from your browser

- Mix and match models with handwritten Rust and/or C/C++ code
- Develop in both state driven or data flow architectures

And Now, target your Pictorus code directly to a New Eagle ECU, as if it were a Raptor target

- Support enabled through HighTec LLVM Toolchain for TriCore




*Pictorus Support Coming To All Of These Great ECU Platforms In the Coming Months*

*Beta Available In Pictorus Today*



GCM111



CCM112



GCM56



GCM112

# Future Hardware Launches





# John Deere VPU2

Available Now!

## Key Functions & Applications

### Key Functions:

- 1x Nvidia Orin AGX (12x ARM)
- 4x CAN2.0
- 1x 100base-T1 Ethernet
- 1x 10G Base-T Ethernet
- 12x GMSL2 Power Over Coax
- 12x GMSL2 6Gbps Camera
- 1 TB Internal SSD
- 64GB LPDDR4 RAM
- 64GB eMMC Flash

### Key Applications:

- Advanced Vision Systems
- High-End Compute

## Advanced Capabilities

### High Performance Compute



- 12x 2.2GHz ARM A78AE
- 2048x 1.3GHz Core GPU
- 64x 1.3GHz Tensor Cores

### Cybersecurity Support

- Nvidia OPTEE

### Environmental Features

- IP66/67
- -25C to +50C operational temperature range





# VPU Roadmap

Available H2 2026

## “VPU Medium”

Key Functions:

- 1x Nvidia Orin NX + AMD ZU7
- 3x CAN
- 1x 100base-T1 Ethernet
- 1x 5G Base-T Ethernet
- 8x camera inputs
- 256GB Internal SSD
- 16GB LPDDR4 RAM

Available Now For Prototyping

## “VPU Lite”

Key Functions:

- 1x AMD ZU7
- 2x CAN
- 1x 1000base-T1 Ethernet
- 1x 100base-T1 Ethernet
- 4x camera inputs
- 32GB eMMC Flash
- 4GB LPDDR4 RAM

## Software Enablement

Linux SDK available initially, able to support the following additional workflows:

- Soft PLC capability through installation of CODESYS
- Ability to develop in Matlab/Simulink including GPU Coder
- Ability to develop in C, C++, Rust, etc

Raptor support will trail hardware availability by 6-9 months

# What's Next





# Raptor Cloud Update


Initial Support in Raptor 2025b

## Raptor Cloud tooling streamlines your development workflow throughout “the V”

Built around a core set of tooling developed by ETAS and available through New Eagle for use within a cloud-based workflow

- Develop your code in Raptor, Matlab/Simulink, ASCET, or C
- Create virtual ECUs of varying fidelity to exercise your software in new ways, even before hardware is available
- Automatically generate living documentation leveraging ETAS eHANDBOOK
- Support multiple workflows with a common set of tooling: Virtual HIL, Virtual Integration Testing, and CI/CD Pipelines.

Combining Raptor Cloud with Raptor-Dev unlocks the ability to create virtual ECUs directly from Raptor with “single button build” efficiency



new eagle



RAPTOR®  
INNOVATION  
SUMMIT 2025